

IN THE CLAIMS:

1. (Canceled)  
2. (Canceled)  
3. (Canceled)  
4. (Canceled)  
5. (Canceled)  
6. (Canceled)  
7. (Canceled)  
8. (Canceled)  
9. (Canceled)  
10. (Canceled)  
11. (Canceled)

Cl  
cont

12. (Currently Amended) The method according to claim 21, wherein the size of the absolute reference section and the local sections comprises 3 to 7 data points per dimensional direction.

13. (Currently Amended) The method according to claim 21, wherein the local sections and/or the absolute reference section are deformed according to a local preferred dip and preferred dip direction.

14. (Canceled)

15. (Currently Amended) The method according to claim 13, wherein during the selection of the absolute reference section, a search is carried out for the dip and dip direction exhibiting the largest similarity among the trace portions belonging to the absolute reference section, whereby afterwards in the determination of the similarity between the absolute reference section and local sections, the specific relative dip between the absolute reference section and the local section conforming to the largest similarity is then determined in each case.

16. (Previously Amended) The method according to claim 13, wherein in addition to the data volume with the similarity values, a data volume with the determined dip values and a further data volume with the determined values of the dip direction are formed.

17. (Currently Amended) The method according to claim 21, wherein the absolute reference section is supplied by a well with ascertained lithological information.

18. (Currently Amended) The method according to claim 17, wherein the absolute reference section is generated synthetically by convolving down a pre-selected 3-dimensional acoustic impedance distribution from the relevant well log with a representative wavelet.

19. (Currently Amended) The method according to claim 17, wherein the absolute reference section is formed synthetically with the help of seismic 3-D modeling techniques from a geological model determined by lithological, petrophysical and/or structural parameters.

C/ 20. (Currently Amended) The method according to claim 21, wherein several different absolute reference sections, ~~for example given by~~ locations of drilled holes, are compared with the local sections, and thus several similarity values are calculated for each data point.

21. (Currently Amended) A method for processing a seismic 3-D measurement data set comprising a multitude of traces, each trace having a sequence of data points provided with amplitude values or acoustic impedances, which comprises the steps of:

(a) selecting an absolute reference section at a predetermined location and depth which comprises neighboring trace portions of several seismic traces;

(b) determining the similarity between the selected absolute reference section and local sections of seismic data from the measurement data set and allocating a similarity value based on the determined similarity to each data point; and

(c) creating a volume of data corresponding with the measurement data set using the similarity value which has been determined and allocated to each data point as the attribute.

22. (Currently Amended) The method according to claim 13, wherein the method comprises before the step of determining the similarity between the absolute reference section and said local section, the step of searching for a specific dip and dip direction for the absolute reference section and each local section which results in the largest similarity of the trace portions from the absolute reference section and each local section, whereby the search comprises an iterative determination of the similarity of neighboring trace portions that are shifted with respect to each other according to dip and dip direction.

[Please add the following claim:]

23. (New) The method according to claim 21, wherein said step of determining similarity includes determining the similarity between several different absolute reference sections which are compared with the local sections, and thus several similarity values are calculated for each data point.

---